

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Fig. 1






Fig. 2




Fig. 3




Fig. 4



FIG. 5




Fig. 6




FIG. 7




FIG. 8

12" of 24awg wire (upphase)
 2 Switch's on off mini Tog.
 2 Red 3000 m.c. LEDs
 2 White 5000 m.c. LEDs
 2 Rubber Boots
 1 'N' style Batt Holder.

OPTICAL ENHANCEMENT SYSTEM




FIG. 9A.




FIG. 9D




FIG. 9B.

Tape Paper Hine
 Drill 2ea 3/16 Holes
 Drill 1 3/16 Hole for wire

Tape sides Below
 Headset Clamps

FIG. 9




FIG. 9E




FIG. 9C

FIG. 10

Net weight w/clip and light
2.5.02/5

